

SUPER SHIELD NICKEL CONDUCTIVE COATING 841-AEROSOL

Material Safety Data Sheet

Section 1: Product and Company Identification

Product Name: Super Shield™ Nickel Conductive Coating **MSDS Code:** 841-Aerosol

Related Part #: 841-340G

Use: Nickel filled electrically conductive coating for reducing EMI/RFI interference and providing electric continuity

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents
USA or CANADA: Call CHEMTREC ☎: **1-800-424-9300**

For emergencies involving dangerous goods; Collect 24/7
CANADA: Call CANUTEC ☎: **1-613-996-6666** or ***666** on cellular phones

Manufacturer: MG Chemicals (Head Office), 9347-193 Street, Surrey, B.C., V4N 4E7

Technical Contacts: ☎ 1-800-201-8822 FAX 1-800-708-9888

E-MAIL: SDS@mgchemicals.com **WEB** www.mgchemicals.com

Section 2: Hazards Identification

WHMIS Classification



A – Aerosol Container; B5 – Flammable Aerosols;
D2A – Very Toxic Material (Carcinogen; Teratogenicity/Embryotoxicity);
D2B – Toxic Material (Skin/Eye Irritation; Skin sensitization)

Note: Carcinogenic effects observed in animal studies for intubation or injection routes of entry, not for normal inhalation route [Oller 2008].

GHS Pictograms



Signal Word
DANGER

Continued on the next page

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

GHS Categories


Criteria	Category	Signal Word	Symbol
Flammable Aerosol	2	Danger	Flame
Specific Target Organ Toxicity Repeated Exposure	1,2	Danger	Exclamation
Eye Irritation	2	Warning	Exclamation
Sensitization Skin sensitizer	1	Warning	Exclamation
Carcinogenicity	2	Warning	Health
Reproductive Toxicity	2	Warning	Health
Specific Target Organ Toxicity Single Exposure	3	Warning	Health
Skin Irritation	3	Warning	—
Acute Toxicity Oral ^{a)}	5	Warning	—
Acute Toxicity Inhalation ^{a)}	5	Warning	—
Environmental Hazard Acute Aqua. Tox.	3	—	—
Environmental Hazard Chronic Aqua. Tox.	3	—	—

a) Base on mixture acute toxicity estimate (ATE)

HMIS RATING

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Physical Hazards

GHS Code: Hazard Statement

H223: Flammable aerosol

H229: Pressurized container: may burst if heated

Health Hazards

GHS Code: Hazard Statement

H319: Causes serious eye irritation

H372: Can damage lungs through prolonged or repeated exposure

H373: May cause damage to central nervous system through prolonged or repeated exposure

H317: May cause allergic skin reaction

H351: Suspected of causing cancer

Continued on the next page

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

H361: Suspected of damaging fertility or the unborn child

H336: May cause drowsiness and dizziness

H316: Causes mild skin irritation

H335: May cause respiratory irritation

H303 + H333: May be harmful if swallowed or inhaled

Eyes Causes severe eye irritation if splashed in eyes or exposed to vapors. May also cause eye redness or pain. The coating contains mechanically abrasive particles.

Skin May cause mild to moderate skin irritation and skin allergies.

Inhalation May cause nose, throat and lung irritation. Inhalation of mist may cause irritation to the upper respiratory tract.

Ingestion *Not a likely route of exposure.* Harmful if swallowed. It is a central nervous system depressant. It may cause irritation and burning sensation.

Chronic Prolonged and repeated exposure to the solvents used may cause dermatitis, defatting of the skin, adverse central nervous systems effects. Extreme doses can cause bladder, liver, and kidney damage.

Inhalation of mist containing nickel particles of less than 0.1 mm may cause chronic inflammation, lung fibrosis, and accumulation of the nickel particles. Nickel is classified as a suspect carcinogen based on animal intratracheal instillation (intubation) or interperitoneal (in body cavity) injection studies. A reliable 2008 study by Oller *et al.* shows no carcinogenicity for the nickel metal via normal inhalation route.

Ingestion of this paint material or inhalation of its mist or vapors during pregnancy may increase the chances of fetal death and of developmental defects.

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

Section 3: Hazardous Ingredients

CAS #	Chemical Name	Wt%	ACGIH TWA	OSHA PEL	STEL
811-97-2	1,1,1,2-tetrafluoroethane	30-60%	[1000 ppm] ^{a)}	N/E	N/E
7440-02-0	nickel	10-30%	1.5 mg/m ³	1.0 mg/m ³ ^{b)}	N/E
67-64-1	2-propanone	10-30%	500 ppm	1000 ppm	750 ppm ^{c)}
108-88-3	toluene	3-7%	20 ppm	200 ppm	150 ppm ^{d)}
110-19-0	isobutyl acetate	1-5%	N/E	N/E	N/E
110-43-0	2-heptanone	1-5%	N/E	N/E	N/E
64-17-5	ethanol	0.5-1.5%	1000 ppm	1000 ppm	N/E
141-78-6	ethyl acetate	0.1-1%	400 ppm	N/E	N/E

Note: Limits from by RTECS database of the Canadian Centre for Occupational Health and Safety (CCOHS). Data from suppliers' MSDS were also consulted.

- a) MG Chemicals established limit corresponding to prevalent international value; no established limit by ACGIH.
- b) Limit presented is for dust or mist
- c) ACGIH STEL
- d) NIOSH STEL; Vacated (retracted) OSHA STEL of 150 ppm; International standard STEL range 100 ppm to 300 ppm

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

Section 4: First Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF INHALED	P304
Symptoms	Immediate: <i>dizziness, drowsiness, headaches, nausea, cough, blurred vision, fatigue</i>
Response	P340: Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.
If feeling unwell	P312: Call a POISON CENTRE/doctor
If exposed or concerned	P313: Get medical advice.
IF IN EYES	P305
Symptoms	Immediate: <i>irritation, redness, pain, blurred vision</i>
Response	P351: Rinse cautiously with water for several minutes. P338: Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists	P313: Get medical attention.
IF ON SKIN	P302
Symptoms	Immediate: <i>irritation, pain, redness;</i> Delayed: <i>dry skin, rash</i>
Response	P362+ P364: Take off contaminated clothing and wash it before reuse. P352: Wash with plenty of water.
If skin irritation or rash persists	P313: Get medical attention.
IF SWALLOWED	P301 (<i>Not a likely route of exposure under normal use</i>)
Symptoms	Immediate: <i>nausea, vomiting, abdominal cramps, irritation, burning sensation, or dizziness</i>
Response	P312: Call a POISON CENTRE/doctor if you feel unwell. P330: Rinse mouth. P331: Do NOT induce vomiting.
If exposed or concerned	P313: Get medical advice.

Note: GHS codes and corresponding precaution statements are used when available.

SUPER SHIELD NICKEL CONDUCTIVE COATING**841-AEROSOL****Section 5: Fire Fighting Measures**

Autoignition Temperature ^{a)}	≥363 °C [685 °F]	Flash Point ^{b)}	-18 °C [-0.4 °F]	LFL [LEL] ^{c)}	2%
				UFL [UEL]	12%

In case of fire P370**Response** P378: Use dry chemical, carbon dioxide, or chemical foam to extinguish.**Combustion Products** Produces CO, CO₂, nitrous oxides, nickel oxides, and smoke. May produce a very toxic nickel carbonyl gas in presence of CO.**Fire-Fighter** Wear self-contained breathing apparatus for fire fighting**General Information** Will burn if involved in a fire. Pressurized container may explode if heated in fire. Vapors are heavier than air, and may travel to sources of ignition near the ground.

Note: The GHS codes and the GHS precaution statements are used. The format is
GHS Codes: Statements.

- a) Values based on ethanol, which is the component with the lowest autoignition value.
b) Lower bound FP estimate is based on the closed cup value for the acetone component.
c) LFL = Lower Flammability [or Explosion] Limit (in volume %);
UFL = Upper Flammability [or Explosion] Limit (in volume %)

Section 6: Accidental Release Measures**Personal Protection:** See Section 8. Avoid breathing fume/mist/vapors.**Containment** Remove all sources of ignition.**Cleaning** Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe up further residue with paper towel and place in container. Wash spill area with soap and water to remove the last traces of residue.**RECOMMENDATION:** A metal container is suggested.**Disposal** Dispose of spill waste according to Section 13.

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

Section 7: Handling and Storage

- Prevention** P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P261 + P271 + P284: Avoid breathing mist/vapors. Use only outdoors or in well ventilated area. In cases of inadequate ventilation wear respiratory protection.
- P270: Do not eat, drink, or smoke when using this product.
- Handling** P280: Wear protective gloves/clothing/eye protection.
- P242 + P243: Use non-sparking tools. Take precautionary measures against static discharge.
- P264: Wash hands thoroughly after handling.
- Storage** P411+ P403 + P235: Store at temperatures not exceeding 40 °C [104 °F] Protect from sunlight. Store in a well-ventilated area.
- RECOMMENDATION** : Store in dry area. Do NOT store at temperatures below or equal to -26.5 °C [-15.7 °F] since this may crush and damage the container.

Section 8: Exposure Controls/Personal Protection

Routes of Entry

Eyes, ingestion, inhalation, and skin

Engineering Controls

Ventilation Keep airborne concentrations below exposure limits given in Section 3.

RECOMMENDATION: Respect the time weighted average of 20 ppm for toluene.

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Continued on the next page

SUPER SHIELD NICKEL CONDUCTIVE COATING 841-AEROSOL

Skin Protection Wear appropriate protective clothing to prevent skin contact.

RECOMMENDATION: Use of protective gloves in butyl rubber, latex, neoprene, or other chemically resistant gloves.

Respiratory Protection If the exposure limits are exceeded or exposed to mist, wear respirator such as a half-mask respirator.

RECOMMENDATION: Consult your local safety supply store to ensure your respirator has filter cartridges appropriate for the ingredients listed in section 3 of this MSDS, and that the respirator is fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Odor	Benzene like, sweetish	Odor Threshold	2 ppm
Appearance	Steel grey	Specific Gravity	1.24	Freezing Point	Not established
Boiling Point ^{a)}	≥56 °C	Vapor Pressure @ 21 °C ^{b)}	1.4 kPa [0.2 lb/in ²]	Evaporation Rate	fast
Autoignition Temperature ^{c)}	≥363 °C [685 °F]	Flash Point ^{a)}	-18 °C [-0.4 °F]	Vapor Density ^{b)}	≥2 (Air =1)
Lower Flammability Limit ^{d)}	2%	Upper Flammability Limit ^{d)}	12%	Decomposition Temp.	Not available
Viscosity	Not established	Partition Coefficient	Not established	Solubility in Water	Partially soluble
pH	7				

a) Values for closed cup flash point and other threshold is based on acetone.

b) Values estimated with literature values of volatile components and by Raoult's Law

c) Values for based on ethanol, which is the component with the lowest autoignition value

d) Lower and Upper Explosive Limits of mixture calculated using Le Chatelier principle and component LFL and UFL limits

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

Section 10: Stability and Reactivity

Stabilities	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Temperatures greater than 40 °C, ignition sources, and incompatible substances
Incompatibilities	Strong oxidizing agents, strong acids, strong bases, ammonium nitrate, perchlorates, phosphorus, selenium, and sulfur
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

Section 11: Toxicological Information

Skin corrosion/irritation	Skin irritant. Prolonged or repeated skin contact may cause dermatitis
Serious eye damage/irritation	Causes serious eye irritation and lesions. Contains mechanically abrasive particles.
Sensitization (allergic reactions)	Nickel may cause skin sensitization in humans
Carcinogenicity (risk of cancer)	Elemental Nickel [7440-02-0] IARC Group 2B: Possibly carcinogenic to humans ACGIH A5: Not suspected as human carcinogen CA Prop 65: Listed as a carcinogen NTP: Reasonably anticipated to be a human carcinogen
Mutagenicity (risk of heritable genetic effects)	Not known
Reproductive Toxicity (risk to sex functions)	Toluene studies on animals show reproductive and developmental hazards at high doses (TDLo ≥ 800 mg/m ³ by inhalation and)
Teratogenicity (risk of fetus malformation)	Harmful to unborn fetus in large doses
STOT-single exposure	Inhalation of toluene may affect the central nervous system
STOT-repeated exposure	Nickel particles can damage the lungs. Toluene may cause damage to organs through prolonged or repeated exposure.

Continued on the next page

SUPER SHIELD NICKEL CONDUCTIVE COATING 841-AEROSOL

Aspiration hazard

Category 1 components <10%;
therefore, it is not classified as aspiration hazard.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation	TCLo inhalation ^{a)}
1,1,1,2-tetrafluoroethane	N/E	N/E	1,500 g/m ³ 4 h Rat	N/E
nickel	5,000 mg/kg Rat	N/E	N/E	10 mg/m ³ 2 h Mouse
2-propanone	5,800 mg/kg Rat	>9,400 µL/kg Guinea pig	44 g/m ³ 4 h Rat	10 mg/m ³ 6 h Human
	5,340 mg/kg Rabbit		50.1 g/m ³ 8 h Rat	30 g/m ³ 2 h Rat
toluene	636 mg/kg Rat	12,124 mg/kg Rabbit	49 g/m ³ 4h Rat	200 ppm Human
isobutyl acetate	13,400 mg/kg Rat	>17,400 mg/kg Rabbit	N/E	8,000 ppm 4h Rat LCLo ^{b)}
2-heptanone	1,670 mg/kg Rat	12,600 µL/kg Rabbit	N/E	7,000 mg/m ³ 4 h Guinea pig
	730 mg/kg Mouse			
ethanol	7,060 mg/kg Rat	N/E	20,000 ppm 10 h Rat	2,500 mg/m ³ 20 min Human
	3,450 mg/kg Mouse		39 g/m ³ 4 h Mouse	50,000 mg/m ³ 2 h Mouse
ethyl acetate	5,620 mg/kg Rat	>20,000 µL/kg Rabbit	45 g/m ³ 2 h Mouse	1,105 mg/m ³ 4 h Rat
	4,100 mg/kg Mouse			

Note: Representative toxicity data from by RTECS database of the Canadian Centre for Occupational Health and Safety (CCOHS) data from supplier MSDS were also consulted.

- a) Lowest toxic airborne concentration tested
- b) Lowest lethal airborne concentration tested

SUPER SHIELD NICKEL CONDUCTIVE COATING**841-AEROSOL****Section 12: Ecological Information****Acute Ecotoxicity**

Category 2

GHS Code: Hazard Statement

H412: Harmful to aquatic life with long lasting effects.

P273: Avoid release to the environment.

Chronic Ecotoxicity

Long lasting effect

Biodegradability

Metallic components are not biodegradable.

VOC* (EPA, WHIMS, and Europe) = 10% [118 g/L]

**Regulated Volatile Organic Compound Content*

Note: Nickel can be recovered from the waste to reclaim the value of the nickel.

Section 13: Disposal Information

GHS Code: Disposal Statement

P501: Dispose of contents in accordance with all local, provincial, state, and federal regulations.

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

Section 14: Transport Information

Ground (less than 4 liter size)

Consumer Commodity; ORM-D

Recommend Shipper be trained and certified. Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA CFR 49 Regulations** (Parts 100 to 185).

Air

Shipper must be trained and certified. Refer to IATA Dangerous Goods Regulations.

UN number: UN1950; **Shipping Name:** AEROSOL, flammable; **Class:** 2.1, Flash Point = -18 °C

Sea

Shipper must be trained and certified. Refer to IMDG regulations.

UN number: UN1950; **Shipping Name:** AEROSOL, flammable; **Class:** 2.1, Flash Point = -18 °C

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Continued on the next page

SUPER SHIELD NICKEL CONDUCTIVE COATING**841-AEROSOL****USA****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product contains toluene (CAS# 108-88-3), which is listed as hazardous air pollutants.

EPCRA (Emergency Planning and Community Right to Know Act, USA, 40 CFR 372.45)

This product contains toluene (CAS# 108-88-3) and nickel (CAS# 7440-02-0), which are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product contains toluene, which is listed as reproductively toxic.

This product contains nickel, which is listed as a carcinogen.

Europe**RoHS** (Restriction of Hazardous Substance Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

SUPER SHIELD NICKEL CONDUCTIVE COATING

841-AEROSOL

Section 16: Other Information

Prepared by	Michel Hachey
Date of Revision	01 May 2013
Supersedes	Version 2.01; 23 April 2012
Reasons for Changes	Updated emergency contact number in section 1 and corrected storage temperature recommendation in section 7.
References	All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Oller, AR; Kirkpatrick, DT; Radovksy, A; and Bates, HK, *Toxicology and Applied Pharmacology*, **233** (262-275) 2008.

Abbreviations

GHS: Globally Harmonized System of Classification of Labeling of Chemicals

LC50 Lethal Concentration 50%

LCLo Lowest Lethal *Airborne* Concentration *Tested*

LD50 Lethal Dose 50%

N/A Not Applicable

N/E Not Estimated

PEL Permissible Exposure Limit

STEL Short-Term Exposure Limit

TCLo Lowest Toxic *Airborne* Concentration *Tested*

TWA Time Weighted Average

VOC Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: SDS@mgchemicals.com or support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. M.G. Chemicals, Inc. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with federal, state, and local regulations.