



Close this window

MSDS

**Common Name:** DEM-KOTE CHROME ALUMINUM, GR06MT4300

**Manufacturer:** SEYMOUR OF SYCAMORE

**MSDS Revision Date:** 10/30/2006

**Grainger Item Number(s):** 6MT43

**Manufacturer Model Number(s):** GR06MT4300

## MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

- [1 IDENTIFICATION OF SUBSTANCE](#)
- [2 COMPOSITION/DATA ON COMPONENTS](#)
- [3 HAZARDS IDENTIFICATION](#)
- [4 FIRST AID MEASURES](#)
- [5 FIRE FIGHTING MEASURES](#)
- [6 ACCIDENTAL RELEASE MEASURES](#)
- [7 HANDLING AND STORAGE](#)
- [8 EXPOSURE CONTROLS AND PERSONAL PROTECTION](#)
- [9 PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10 STABILITY AND REACTIVITY](#)
- [11 TOXICOLOGICAL INFORMATION](#)
- [12 ECOLOGICAL INFORMATION](#)
- [13 DISPOSAL CONSIDERATIONS](#)
- [14 TRANSPORT INFORMATION](#)
- [15 REGULATIONS](#)
- [16 OTHER INFORMATION](#)

S (R\*)  
SEYMOUR (R\*)

MATERIAL SAFETY DATA SHEET

ACC. TO ISO/DIS 11014

PRINTING DATE: 11/02/2006

REVIEWED ON: 10/30/2006

## 1 IDENTIFICATION OF SUBSTANCE



TRADE NAME: DEM-KOTE CHROME ALUMINUM

PRODUCT CODE: GR06MT4300

MANUFACTURER/SUPPLIER:  
SEYMOUR OF SYCAMORE  
917 CROSBY AVENUE  
SYCAMORE, IL 60178  
(815)-895-9101

WWW.SEYMOURPAINT.COM

INFORMATION DEPARTMENT: HEALTH & SAFETY DEPARTMENT

EMERGENCY INFORMATION:

CHEMTEL: 1-800-255-3924, 813-248-0585 IF LOCATED OUTSIDE THE U.S.

## 2 COMPOSITION/DATA ON COMPONENTS



CHEMICAL DESCRIPTION:

THIS PRODUCT IS A MIXTURE OF THE SUBSTANCES LISTED BELOW WITH NONHAZARDOUS ADDITIONS.

DANGEROUS COMPONENTS:

108-88-3	TOLUENE	35.87%
74-98-6	PROPANE	20.79%
106-97-8	n-BUTANE	12.21%
9011-11-4	HYDROCARBON RESIN	10.38%
67-64-1	ACETONE	10.38%
64742-47-8	MINERAL SPIRITS	6.86%
7429-90-5	ALUMINUM FLAKE	2.45%
64742-89-8	VM&P NAPHTHA	1.05%

ADDITIONAL INFORMATION:

FOR THE WORDING OF THE LISTED RISK PHRASES REFER TO SECTION 3.

## 3 HAZARDS IDENTIFICATION



HAZARD DESCRIPTION:

HARMFUL

EXTREMELY FLAMMABLE

PHYSICAL DANGERS:

HAS A NARCOTIZING EFFECT.

EXTREMELY FLAMMABLE LIQUID AND VAPOR IN A PRESSURIZED CONTAINER. KEEP AWAY FROM HEAT, SPARKS, AND FLAME.

EXTREMELY FLAMMABLE.

IRRITATING TO SKIN.

KEEP OUT OF THE REACH OF CHILDREN.

EFFECTS OF SHORT-TERM OVEREXPOSURE:

VAPORS CAUSE IRRITATION TO THE EYES, NOSE, THROAT, SKIN, AND CENTRAL NERVOUS SYSTEM. SYMPTOMS MAY INCLUDE DIZZINESS, THROAT IRRITATION, HEADACHE, FATIGUE, SWELLING OF EYES, AND NAUSEA.

EFFECTS OF CHRONIC OVEREXPOSURE:

MAY CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. REPEATED OVEREXPOSURE CAN ALSO DAMAGE KIDNEYS, LUNGS. LIVER, HEART, AND BLOOD. INTENTIONAL MISUSE BY DELIBERATELY INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

NFPA RATINGS (SCALE 0 - 4):

HEALTH 1  
FIRE 4  
REACTIVITY 3

## HMIS-RATINGS (SCALE 0 - 4):

HEALTH 1  
FIRE 4  
PHYSICAL HAZARD 3

**4 FIRST AID MEASURES**

AFTER INHALATION: IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN.

AFTER SKIN CONTACT:  
IMMEDIATELY WASH WITH WATER AND SOAP AND RINSE THOROUGHLY.

AFTER EYE CONTACT:  
RINSE OPENED EYE FOR SEVERAL MINUTES UNDER RUNNING WATER. THEN CONSULT A DOCTOR.

AFTER SWALLOWING: CONTACT PHYSICIAN OR POISON CONTROL CENTER.

**5 FIRE FIGHTING MEASURES**

EXTINGUISHING AGENTS:  
CO2. SAND, EXTINGUISHING POWDER, OR WATER SPRAY. FIGHT LARGER FIRES WITH WATER SPRAY OR ALCOHOL RESISTANT FOAM.

PROTECTIVE EQUIPMENT: NO SPECIAL MEASURES REQUIRED.

**6 ACCIDENTAL RELEASE MEASURES**

PERSONAL SAFETY PRECAUTIONS:  
WEAR PROTECTIVE EQUIPMENT. KEEP UNPROTECTED PERSONS AWAY.

ENVIRONMENTAL SAFETY PRECAUTIONS:  
INFORM APPROPRIATE AUTHORITIES IN CASE OF SEEPAGE INTO WATER COURSE OR SEWAGE SYSTEM.

DO NOT ALLOW PRODUCT TO REACH SEWAGE SYSTEMS OR GROUND WATER.

MEASURES FOR CLEANING/COLLECTING:  
DO NOT FLUSH WITH WATER OR AQUEOUS CLEANSING AGENTS. USE DILUTED CAUSTIC SOLUTION. SOAK UP SPILLS WITH INERT ABSORBENT MATERIAL. REFER TO SECTION 13 FOR DISPOSAL INFORMATION.

**7 HANDLING AND STORAGE**

FIRE/EXPLOSION PROTECTION:  
DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL.  
DO NOT SMOKE. PROTECT FROM ELECTROSTATIC CHARGES.

STORAGE REQUIREMENTS:  
OBSERVE PRESSURIZED CONTAINER STORAGE REGULATIONS. CONSULT WITH YOUR LOCAL AUTHORITIES.

KEEP AWAY FROM SOURCES OF HEAT AND DIRECT SUNLIGHT. DO NOT WAREHOUSE IN SUBFREEZING CONDITIONS.

**8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**

## COMPONENTS WITH LIMIT VALUES THAT REQUIRE MONITORING AT THE WORKPLACE:

## 108-88-3 TOLUENE:

## TLV:

SHORT-TERM VALUE: 500 MG/M3, 300 PPM

LONG-TERM VALUE: 375 MG/M3, 200 PPM

## 74-98-6 PROPANE:

PEL: 1800 MG/M3, 1000 PPM

## REL:

SHORT-TERM VALUE: N.E. MG/M3, N.E. PPM

LONG-TERM VALUE: 1800 MG/M3, 1000 PPM

TLV: (4508) MG/M3, (2500) PPM

## 106-97-8 n-BUTANE:

REL: 1900 MG/M3, 800 PPM

TLV: 1900 MG/M3, 800 PPM

## 67-64-1 ACETONE:

## TLV:

SHORT-TERM VALUE: 1782 MG/M3, 750 PPM

LONG-TERM VALUE: 600 MG/M3, 250 PPM

## 64742-47-8 MINERAL SPIRITS:

## TLV:

200 MG/M3

AS TOTAL HYDROCARBON VAPOR; SKIN; (P)

## 7429-90-5 ALUMINUM FLAKE:

PEL: 15\*; 5\*\* MG/M3

\*TOTAL DUST

\*\*RESPIRABLE FRACTION

REL: 10\*; 5\*\* MG/M3 METAL DUST

\*TOTAL DUST

\*\*RESPIRABLE FRACTION

TLV: 10 MG/M3 METAL DUST

## PROTECTIVE HYGIENIC MEASURES:

KEEP AWAY FROM FOODSTUFFS AND ANIMAL FEED. WASH HANDS AFTER USE.

AVOID CONTACT WITH THE SKIN.

## BREATHING EQUIPMENT:

USE SUITABLE RESPIRATORY PROTECTIVE DEVICE IN CASE OF INSUFFICIENT VENTILATION.

A RESPIRATOR IS GENERALLY NOT NECESSARY WHEN USING THIS PRODUCT OUTDOORS OR IN LARGE OPEN AREAS. IN CASES OF INADEQUATE VENTILATION, A RESPIRATORY PROTECTIVE DEVICE SHOULD BE WORN TO PREVENT OVEREXPOSURE.

## PROTECTION OF HANDS:

PROTECTIVE GLOVES. THE GLOVE MATERIAL HAS TO BE IMPERMEABLE AND RESISTANT TO THE SUBSTANCE. NO GLOVE RECOMMENDATION CAN BE GIVEN.

EYE PROTECTION: TIGHTLY SEALED GOGGLES

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**GENERAL INFORMATION:**

FORM: AEROSOL

COLOR: ACCORDING TO TRADE NAME DESCRIPTION IN SECTION 1.

ODOR: SOLVENT

BOILING POINT/BOILING RANGE: -44 DEG. C (-47 DEG. F)

FLASH POINT: -19 DEG. C (-2 DEG. F)

IGNITION TEMPERATURE: 210.0 DEG. C (410 DEG. F)

AUTO IGNITING: PRODUCT IS NOT SELF-IGNITING.

**DANGER OF EXPLOSION:**

STABLE AT NORMAL TEMPERATURES. CAN MAY BURST WHEN EXPOSED TO TEMPERATURES EXCEEDING 120 DEGREES FAHRENHEIT.

IN USE, MAY FORM FLAMMABLE/EXPLOSIVE VAPOR-AIR MIXTURE.

LOWER EXPLOSION LIMIT: 1.5 VOL %

UPPER EXPLOSION LIMIT: 10.9 VOL %

VAPOR PRESSURE: 40 PSI, 2750 HPA

DENSITY: NOT DETERMINED.

SPECIFIC GRAVITY: BETWEEN 0.77 AND 0.90 (WATER EQUALS 1.00)

VOC CONTENT: 409.2 G/L/3.41 LB/GL

VOC IN WEIGHT PERCENT (LESS ACETONE): 40.9%

SOLIDS CONTENT: 13.9%

**10 STABILITY AND REACTIVITY****CONDITIONS TO BE AVOIDED:**

DO NOT ALLOW THE CAN TO EXCEED 120 DEGREES FAHRENHEIT. STABLE AT NORMAL TEMPERATURES.

POSSIBILITY OF HAZARDOUS REACTIONS: NO DANGEROUS REACTIONS KNOWN.

**11 TOXICOLOGICAL INFORMATION**

PRIMARY EFFECT ON THE SKIN: IRRITANT TO SKIN AND MUCOUS MEMBRANES.

PRIMARY EFFECT ON THE EYE: NO IRRITATING EFFECT.

SENSITIZATION: NO SENSITIZING EFFECTS KNOWN.

ADDITIONAL TOXICOLOGICAL INFORMATION: HARMFUL

**12 ECOLOGICAL INFORMATION****OTHER INFORMATION:**

THIS PRODUCT DOES NOT CONTAIN ANY CHLOROFLOUROCARBONS (CFC'S). CHLORINATED SOLVENTS, LEAD, MERCURY. CADMIUM, HEXAVALENT CHROMIUM, POLYBROMINATED

BIPHENYL (PBB), OR POLYBROMINATED DIPHENYL ETHER (PDBE). NO SPECIFIC ECOLOGICAL DATA IS AVAILABLE FOR THIS PRODUCT.

AQUATIC TOXICITY:  
HARMFUL TO AQUATIC ORGANISMS.  
HAZARDOUS FOR WATER, DO NOT EMPTY INTO DRAINS.

### 13 DISPOSAL CONSIDERATIONS



DISPOSAL METHOD:  
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT PUNCTURE, INCINERATE, OR COMPACT. PARTIALLY EMPTY CANS MUST BE DISPOSED OF RESPONSIBLY. DO NOT HEAT OR CUT EMPTY CONTAINERS WITH ELECTRIC OR GAS TORCHES.

RECOMMENDATION: EMPTY CANS SHOULD BE RECYCLED.

### 14 TRANSPORT INFORMATION



HAZARD CLASS: 2.1

IDENTIFICATION NUMBER: N/A

LABEL: 2.1

ADR/RID CLASS: 2 5F GASES

UN-NUMBER: 1950

IMDG CLASS: 2.1

PACKAGING GROUP: II

EMS NUMBER: F-D, S-U

MARINE POLLUTANT: NO

ICAO/IATA CLASS: 2.1

PROPPER SHIPPING NAME:  
AEROSOLS, FLAMMABLE  
CONSUMER COMMODITY ORM-D

### 15 REGULATIONS



SARA SECTION 355 (EXTREMELY HAZARDOUS SUBSTANCES):  
NONE OF THE INGREDIENTS IN THIS PRODUCT ARE LISTED.

SARA SECTION 313 (SPECIFIC TOXIC CHEMICAL LISTINGS):  
NONE OF THE INGREDIENTS IS LISTED.

TSCA (TOXIC SUBSTANCES CONTROL ACT): ALL INGREDIENTS ARE LISTED.

PROPOSITION 65 CHEMICALS KNOWN TO CAUSE CANCER:  
NONE OF THE INGREDIENTS IN THIS PRODUCT ARE LISTED.

PROPOSITION 65:

CHEMICALS KNOWN TO CAUSE DEVELOPMENTAL TOXICITY: 108-88-3 TOLUENE

CANADIAN WHMIS:  
CLASS A, B5 - FLAMMABLE AEROSOLS

## EPA:

A = KNOWN HUMAN CARCINOGEN

B = PROBABLE HUMAN CARCINOGEN

C = POSSIBLE HUMAN CARCINOGEN

D = NOT CLASSIFIABLE AS TO HUMAN CARCINOGENICITY:

INADEQUATE HUMAN AND ANIMAL EVIDENCE OF CARCINOGENICITY (OR NO DATA IS AVAILABLE).

## IARC:

## GROUP 2B:

THE INGREDIENT IS POSSIBLY CARCINOGENIC TO HUMANS. THERE IS LIMITED EVIDENCE OF CARCINOGENICITY.

## GROUP 3:

THE INGREDIENT IS UNCLASSIFIABLE AS TO ITS CARCINOGENICITY TO HUMANS.

## ACGIH TLVS:

A1-DESIGNATES A CONFIRMED HUMAN CARCINOGEN.

A2-DESIGNATES A SUSPECTED HUMAN CARCINOGEN.

A3-DESIGNATES AN ANIMAL CARCINOGEN.

A4-DESIGNATES "NOT CLASSIFIABLE AS A HUMAN CARCINOGEN".

NIOSH: NONE OF THE INGREDIENTS IS LISTED.

**16 OTHER INFORMATION**

THIS INFORMATION IS BASED ON OUR PRESENT KNOWLEDGE. HOWEVER, THIS SHALL NOT CONSTITUTE A GUARANTEE FOR ANY SPECIFIC PRODUCT FEATURES AND SHALL NOT ESTABLISH A LEGALLY VALID CONTRACTUAL RELATIONSHIP.

CONTACT: REGULATORY AFFAIRS

USA