

# MATERIAL SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: **Quick 'n Easy Specialty Adhesive Remover**

Company Name and Address: Auto Tech Mfg., PO Box 757, Grants Pass, Oregon 97528

Usage: Removes uncured epoxies, urethanes and reactive adhesives and cured adhesives such as silicones

Description: Clear liquid with mild cherry-solvent odor, aromatic

Information Telephone: (541) 474-0232

Emergency Telephone: (800) 545-8624

Emergency Facsimile: (541) 474-2410

Revised 1/13 - Replaces 01/10

## 2. PRODUCT COMPOSITION / INGREDIENT INFORMATION

PRODUCT COMPONENTS AND PERCENTAGES ARE PROPRIETARY INFORMATION. Hazardous ingredients as follows:

Petroleum Distillates CAS # 64742-88-7

Dimethyl-benzene CAS # 1330-20-7

Ethylbenzene CAS # 000100-41-4

2-Butoxyethanol CAS # 111-76-2

UPS CLASSIFIED: Consumer Commodity ORM-D under 49 CFR 173.150 (a) & (b)

## 3. HAZARDOUS MATERIAL IDENTIFICATION SYSTEM RATINGS

HMIS and NFPA Hazard Ratings: HEALTH - 3 ..... FLAMMABILITY - 3 ..... REACTIVITY - 0 ..... PERSONAL PROTECTION - 2

## 4. HEALTH INFORMATION AND RECOMMENDED PROTECTION

### PERSONAL PROTECTION AND FIRST AID MEASURES:

- **EYE CONTACT:** Wear safety glasses with side shields, or face mask. Eyewash should be available. May irritate eyes. Flush eyes with large amounts of fresh water for 15 minutes. Get medical attention.
- **SKIN CONTACT:** Wear appropriate clothing. Wear chemical resistant gloves. Safety shower should be available. Prolonged contact may cause skin irritation. Flush area with large amounts of fresh water; use soap. Launder clothing before reuse.
- **INHALATION:** Use NIOSH approved respirator if conditions generate mists or vapors. Use with adequate ventilation. High concentrations may cause irritation to respiratory tract, headaches and dizziness. Remove from exposure to fresh air. Keep at rest. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Call physician immediately.
- **INGESTION:** Do not take internally. May have serious effects if ingested, or aspirated into lungs while vomiting. If ingested, **DO NOT** induce vomiting. Keep at rest. Get immediate medical attention.

## 5. FIRE AND EXPLOSION

**FLASH POINT:** 81 Degrees Fahrenheit METHOD TCC **BOILING POINT:** 197 Degrees Celsius (End Point)

**GENERAL HAZARD: FLAMMABLE LIQUID.** Can form flammable mixtures at temperatures at or above flash point. "Empty" containers retain liquid and/or vapors. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, open flame, sparks, static electricity or other sources of ignition. Empty containers must be properly disposed of.

**EXTINGUISHING MEDIA: DO NOT** use direct water stream. Use water spray, CO<sub>2</sub>, dry chemical or water fog spray. Use NFPA Class B extinguisher for Class I C liquid fire. Use self-contained breathing apparatus and protective clothing. Cool exposed containers with water.

## 6. SPILL CONTROL PROCEDURES

**ACTION:** Wear appropriate clothing and safety equipment. Small Spill: Wipe or mop; dispose of in DOT approved container. Large Spill: Absorb spill sand or other non-combustible waste material; dispose in DOT approved containers. Keep from sewers, storm drains, surface waters and soil.

**DISPOSAL:** Dispose of contaminated product, clean-up materials and empty containers according to Federal, State and Local regulations.

## 7. PHYSICAL / CHEMICAL PROPERTIES

**REACTIVITY:** Stable **CONDITIONS/MATERIALS TO AVOID:** Isolate from oxidizers, heat, sparks, electric equipment, other sources of ignition and open flame.

**HAZARDOUS POLYMERIZATION:** Will not occur.

## 8. STORAGE AND HANDLING

Store in a cool, dry, well-ventilated place away from all heat, flame and ignition sources. Do not store above 120 degrees F. Electrically ground all equipment. Use non-sparking tools. Keep container closed tightly when not in use. "Empty" container retains liquid and/or vapors and is hazardous and must be properly disposed of. Wash thoroughly after using. Avoid skin, eye and mouth contact.

## 9. OTHER INFORMATION

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Fire. All components of this product are on the TSCA list.

SARA TITLE III Section 313 Supplier Notification: This product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 and of 40 CFR 372.

California Proposition 65: This product contains the following chemical known to the State of California to cause cancer: Ethylbenzene.

This document has been prepared according to OSHA Standard 29 CFR 1910-1200. It is your responsibility and legal duty to make all information in this MSDS available to your employees, and to anyone who requests this information after product purchase.

The information contained herein is believed to be accurate, based on current component MSDS knowledge and experience and represents the best information currently available to us. It is provided for purpose of hazard communication as part of a product safety program. It is not intended to constitute performance information concerning this product. No responsibility is assumed that the information is sufficient or correct in all cases. No express or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein and we assume no liability resulting from use of the product. This information and product are provided on the condition that the user shall make determination as to the suitability for a particular purpose, and on the condition that user shall assume all risks of use thereof.